

06B116 22 Neutral

SKU: 24167Z16B22H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
ISO-standaardmaat	06B
designation	06B116 22
Boring diameter (mm)	22
Eenheden	pc
numberOfTeethZ	16
toothWidthMM	5.3
pitchCircleDiameterMM	48.82
tipCircleDiameterMM	52.5
Geharde tanden	Ja
Gewicht (kg)	0.18
weldedHub	Nee
taperBushSize	
hubDiamDnMM	37
lengthInclHubLnMM	28
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M5
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101330016022
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
Boring diameter (mm)	22
Geharde tanden	Ja
Gewicht (kg)	0.18

Beschrijving

06B Simplex Z 16, Standard Finished Bore 22 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/06b116-22-neutral/>