

06B116 24 Neutral

SKU: 24167Z16B24H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
ISO-standaardmaat	06B
designation	06B116 24
Boring diameter (mm)	24
Eenheden	pc
numberOfTeethZ	16
toothWidthMM	5.3
pitchCircleDiameterMM	48.82
tipCircleDiameterMM	52.5
Geharde tanden	Ja
Gewicht (kg)	0.21
weldedHub	Nee
execution	*
taperBushSize	
hubDiamDnMM	42
lengthInclHubLnMM	28

keywayAccToDIN6885/1	Ja
boreDiameterTol	H7
keywayTol	H9
setscrewSize	M6
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101330016024
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
Boring diameter (mm)	24
Geharde tanden	Ja
Gewicht (kg)	0.21

Beschrijving

06B Simplex Z 16, Standard Finished Bore 24 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/06b116-24-neutral/>