

06B116 Neutral

SKU: 200KHG67Z16



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
ISO-standaardmaat	ISO 606
designation	06B116
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	16
toothWidthMM	5.3
pilotBoreDiameterMM	10
pitchCircleDiameterMM	48.82
tipCircleDiameterMM	52.5
Geharde tanden	Ja
Gewicht (kg)	0.24
weldedHub	Nee
taperBushSize	
hubDiamDnMM	37
lengthInclHubLnMM	37

SprocketType	Standard Induction hardened teeth
BEAArticleNumber	191330016
ISOstandardSize2	06B
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
Boring diameter (mm)	
Geharde tanden	Ja
Gewicht (kg)	0.24

Beschrijving

ISO 606 Simplex Z 16, Standard Induction hardened teeth Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/06b116-neutral-2/>