

06B120 20 Neutral

SKU: 24167Z20B20H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
ISO-standaardmaat	06B
designation	06B120 20
Boring diameter (mm)	20
Eenheden	pc
numberOfTeethZ	20
toothWidthMM	5.3
pitchCircleDiameterMM	60.89
tipCircleDiameterMM	64.6
Geharde tanden	Ja
Gewicht (kg)	0.34
weldedHub	Nee
taperBushSize	
hubDiamDnMM	46
lengthInclHubLnMM	28
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M5
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101330020020
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
Boring diameter (mm)	20
Geharde tanden	Ja
Gewicht (kg)	0.34

Beschrijving

06B Simplex Z 20, Standard Finished Bore 20 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/06b120-20-neutral/>