

06B122 Neutral

SKU: 200KHG67Z22



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
ISO-standaardmaat	ISO 606
designation	06B122
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	22
toothWidthMM	5.3
pilotBoreDiameterMM	12
pitchCircleDiameterMM	66.93
tipCircleDiameterMM	70.6
Geharde tanden	Ja
Gewicht (kg)	0.46
weldedHub	Nee
taperBushSize	
hubDiamDnMM	50
lengthInclHubLnMM	50

SprocketType	Standard Induction hardened teeth
BEAArticleNumber	191330022
ISOstandardSize2	06B
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
Boring diameter (mm)	
Geharde tanden	Ja
Gewicht (kg)	0.46

Beschrijving

ISO 606 Simplex Z 22, Standard Induction hardened teeth Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/06b122-neutral-2/>