

06B124 19 Neutral

SKU: 24167Z24B19H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
ISO-standaardmaat	06B
designation	06B124 19
Boring diameter (mm)	19
Eenheden	pc
numberOfTeethZ	24
toothWidthMM	5.3
pitchCircleDiameterMM	72.97
tipCircleDiameterMM	76.7
Geharde tanden	Ja
Gewicht (kg)	0.51
weldedHub	Nee
taperBushSize	
hubDiamDnMM	54
lengthInclHubLnMM	28
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M5
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101330024019
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
Boring diameter (mm)	19
Geharde tanden	Ja
Gewicht (kg)	0.51

Beschrijving

06B Simplex Z 24, Standard Finished Bore 19 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/06b124-19-neutral/>