

06B125 24 Neutral

SKU: 24167Z25B24H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
ISO-standaardmaat	06B
designation	06B125 24
Boring diameter (mm)	24
Eenheden	pc
numberOfTeethZ	25
toothWidthMM	5.3
pitchCircleDiameterMM	76
tipCircleDiameterMM	79.7
Geharde tanden	Ja
Gewicht (kg)	0.53
weldedHub	Nee
taperBushSize	
hubDiamDnMM	57
lengthInclHubLnMM	28
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M6
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101330025024
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
Boring diameter (mm)	24
Geharde tanden	Ja
Gewicht (kg)	0.53

Beschrijving

06B Simplex Z 25, Standard Finished Bore 24 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/06b125-24-neutral/>