

06B125 Neutral

SKU: 200KHG67Z25



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
ISO-standaardmaat	ISO 606
designation	06B125
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	25
toothWidthMM	5.3
pilotBoreDiameterMM	12
pitchCircleDiameterMM	76
tipCircleDiameterMM	79.7
Geharde tanden	Ja
Gewicht (kg)	0.6
weldedHub	Nee
taperBushSize	
hubDiamDnMM	57
lengthInclHubLnMM	57

SprocketType	Standard Induction hardened teeth
BEAArticleNumber	191330025
ISOstandardSize2	06B
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
Boring diameter (mm)	
Geharde tanden	Ja
Gewicht (kg)	0.6

Beschrijving

ISO 606 Simplex Z 25, Standard Induction hardened teeth Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/06b125-neutral-2/>