

06B130 20 Neutral

SKU: 24167Z30B20H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
ISO-standaardmaat	06B
designation	06B130 20
Boring diameter (mm)	20
Eenheden	pc
numberOfTeethZ	30
toothWidthMM	5.3
pitchCircleDiameterMM	91.12
tipCircleDiameterMM	94.8
Geharde tanden	Ja
Gewicht (kg)	0.74
weldedHub	Nee
taperBushSize	
hubDiamDnMM	60
lengthInclHubLnMM	30
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M5
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101330030020
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
Boring diameter (mm)	20
Geharde tanden	Ja
Gewicht (kg)	0.74

Beschrijving

06B Simplex Z 30, Standard Finished Bore 20 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/06b130-20-neutral/>