

06B130 Neutral

SKU: 200KHG67Z30



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
ISO-standaardmaat	ISO 606
designation	06B130
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	30
toothWidthMM	5.3
pilotBoreDiameterMM	12
pitchCircleDiameterMM	91.12
tipCircleDiameterMM	94.8
Geharde tanden	Ja
Gewicht (kg)	0.72
weldedHub	Nee
taperBushSize	
hubDiamDnMM	60
lengthInclHubLnMM	60

SprocketType	Standard Induction hardened teeth
BEAArticleNumber	191330030
ISOstandardSize2	06B
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/8"
Spoed (mm)	9.525
Boring diameter (mm)	
Geharde tanden	Ja
Gewicht (kg)	0.72

Beschrijving

ISO 606 Simplex Z 30, Standard Induction hardened teeth Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/06b130-neutral-2/>