

08B120 30 Neutral

SKU: 24185Z20B30H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	1/2"
Spoed (mm)	12.7
ISO-standaardmaat	08B
designation	08B120 30
Boring diameter (mm)	30
Eenheden	pc
numberOfTeethZ	20
toothWidthMM	7.2
pitchCircleDiameterMM	81.19
tipCircleDiameterMM	86
Geharde tanden	Ja
Gewicht (kg)	0.65
weldedHub	Nee
taperBushSize	
hubDiamDnMM	64
lengthInclHubLnMM	28
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M6
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101340020030
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1/2"
Spoed (mm)	12.7
Boring diameter (mm)	30
Geharde tanden	Ja
Gewicht (kg)	0.65

Beschrijving

08B Simplex Z 20, Standard Finished Bore 30 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/08b120-30-neutral/>