

08B122 30 Neutral

SKU: 24185Z22B30H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	1/2"
Spoed (mm)	12.7
ISO-standaardmaat	08B
designation	08B122 30
Boring diameter (mm)	30
Eenheden	pc
numberOfTeethZ	22
toothWidthMM	7.2
pitchCircleDiameterMM	89.24
tipCircleDiameterMM	94.1
Geharde tanden	Ja
Gewicht (kg)	0.81
weldedHub	Nee
taperBushSize	
hubDiamDnMM	70
lengthInclHubLnMM	28
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M6
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101340022030
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1/2"
Spoed (mm)	12.7
Boring diameter (mm)	30
Geharde tanden	Ja
Gewicht (kg)	0.81

Beschrijving

08B Simplex Z 22, Standard Finished Bore 30 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/08b122-30-neutral/>