

## 08B124 30 Neutral

SKU: 24185Z24B30H



### Specificaties

|                        |           |
|------------------------|-----------|
| Kettingsontwerp        | Simplex   |
| Oppervlaktebehandeling | NO        |
| Materiaal              | C45       |
| Spoed (inch)           | 1/2"      |
| Spoed (mm)             | 12.7      |
| ISO-standaardmaat      | 08B       |
| designation            | 08B124 30 |
| Boring diameter (mm)   | 30        |
| Eenheden               | pc        |
| numberOfTeethZ         | 24        |
| toothWidthMM           | 7.2       |
| pitchCircleDiameterMM  | 97.29     |
| tipCircleDiameterMM    | 102.1     |
| Geharde tanden         | Ja        |
| Gewicht (kg)           | 0.88      |
| weldedHub              | Nee       |
| taperBushSize          |           |
| hubDiamDnMM            | 70        |
| lengthInclHubLnMM      | 28        |
| keywayAccToDIN6885/1   | Ja        |

|                                                      |                        |
|------------------------------------------------------|------------------------|
| <b>boreDiameterTol</b>                               | H7                     |
| <b>keywayTol</b>                                     | H9                     |
| <b>setscrewSize</b>                                  | M6                     |
| <b>SprocketType</b>                                  | Standard Finished Bore |
| <b>BEAArticleNumber</b>                              | SB101340024030         |
| <b>ISOstandardSize2</b>                              | ISO 606                |
| <b>brandType(extraAttributeForNeutralIdentifier)</b> | Extended               |
| <b>Merk</b>                                          | Neutral                |
| <b>Materiaal</b>                                     | C45                    |
| <b>Spoed (inch)</b>                                  | 1/2"                   |
| <b>Spoed (mm)</b>                                    | 12.7                   |
| <b>Boring diameter (mm)</b>                          | 30                     |
| <b>Geharde tanden</b>                                | Ja                     |
| <b>Gewicht (kg)</b>                                  | 0.88                   |

## Beschrijving

08B Simplex Z 24, Standard Finished Bore 30 Neutral Sprockets

## Product URL

<https://aandrijftechniek.nl/product/08b124-30-neutral/>