

08B125 32 Neutral

SKU: 24185Z25B32H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	1/2"
Spoed (mm)	12.7
ISO-standaardmaat	08B
designation	08B125 32
Boring diameter (mm)	32
Eenheden	pc
numberOfTeethZ	25
toothWidthMM	7.2
pitchCircleDiameterMM	101.33
tipCircleDiameterMM	106.2
Geharde tanden	Ja
Gewicht (kg)	0.9
weldedHub	Nee
taperBushSize	
hubDiamDnMM	70
lengthInclHubLnMM	28
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M8
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101340025032
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1/2"
Spoed (mm)	12.7
Boring diameter (mm)	32
Geharde tanden	Ja
Gewicht (kg)	0.9

Beschrijving

08B Simplex Z 25, Standard Finished Bore 32 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/08b125-32-neutral/>