

10B110 15 Neutral

SKU: 24110Z10B15H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	10B
designation	10B110 15
Boring diameter (mm)	15
Eenheden	pc
numberOfTeethZ	10
toothWidthMM	9.1
pitchCircleDiameterMM	51.37
tipCircleDiameterMM	58.3
Geharde tanden	Ja
Gewicht (kg)	0.21
weldedHub	Nee
taperBushSize	
hubDiamDnMM	35
lengthInclHubLnMM	25
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M4
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101350010015
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	15
Geharde tanden	Ja
Gewicht (kg)	0.21

Beschrijving

10B Simplex Z 10, Standard Finished Bore 15 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b110-15-neutral/>