

10B110 24 Neutral

SKU: 24110Z10B24H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	10B
designation	10B110 24
Boring diameter (mm)	24
Eenheden	pc
numberOfTeethZ	10
toothWidthMM	9.1
pitchCircleDiameterMM	51.37
tipCircleDiameterMM	58.3
Geharde tanden	Ja
Gewicht (kg)	0.21
weldedHub	Nee
execution	*
taperBushSize	
hubDiamDnMM	42
lengthInclHubLnMM	25

keywayAccToDIN6885/1	Ja
boreDiameterTol	H7
keywayTol	H9
setscrewSize	M6
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101350010024
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	24
Geharde tanden	Ja
Gewicht (kg)	0.21

Beschrijving

10B Simplex Z 10, Standard Finished Bore 24 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b110-24-neutral/>