

10B111 28 Neutral

SKU: 24110Z11B28H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	10B
designation	10B111 28
Boring diameter (mm)	28
Eenheden	pc
numberOfTeethZ	11
toothWidthMM	9.1
pitchCircleDiameterMM	56.34
tipCircleDiameterMM	63.2
Geharde tanden	Ja
Gewicht (kg)	0.27
weldedHub	Nee
execution	*
taperBushSize	
hubDiamDnMM	47
lengthInclHubLnMM	30

keywayAccToDIN6885/1	Ja
boreDiameterTol	H7
keywayTol	H9
setscrewSize	M6
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101350011028
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	28
Geharde tanden	Ja
Gewicht (kg)	0.27

Beschrijving

10B Simplex Z 11, Standard Finished Bore 28 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b111-28-neutral/>