

10B112 30 Neutral

SKU: 24110Z12B30H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	10B
designation	10B112 30
Boring diameter (mm)	30
Eenheden	pc
numberOfTeethZ	12
toothWidthMM	9.1
pitchCircleDiameterMM	61.34
tipCircleDiameterMM	68.2
Geharde tanden	Ja
Gewicht (kg)	0.32
weldedHub	Nee
execution	*
taperBushSize	
hubDiamDnMM	51
lengthInclHubLnMM	30

keywayAccToDIN6885/1	Ja
boreDiameterTol	H7
keywayTol	H9
setscrewSize	M6
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101350012030
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	30
Geharde tanden	Ja
Gewicht (kg)	0.32

Beschrijving

10B Simplex Z 12, Standard Finished Bore 30 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b112-30-neutral/>