

10B113 28 Neutral

SKU: 24110Z13B28H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	10B
designation	10B113 28
Boring diameter (mm)	28
Eenheden	pc
numberOfTeethZ	13
toothWidthMM	9.1
pitchCircleDiameterMM	66.32
tipCircleDiameterMM	73.2
Geharde tanden	Ja
Gewicht (kg)	0.36
weldedHub	Nee
taperBushSize	
hubDiamDnMM	47
lengthInclHubLnMM	30
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M6
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101350013028
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	28
Geharde tanden	Ja
Gewicht (kg)	0.36

Beschrijving

10B Simplex Z 13, Standard Finished Bore 28 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b113-28-neutral/>