

10B113 32 Neutral

SKU: 24110Z13B32H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	10B
designation	10B113 32
Boring diameter (mm)	32
Eenheden	pc
numberOfTeethZ	13
toothWidthMM	9.1
pitchCircleDiameterMM	66.32
tipCircleDiameterMM	73.2
Geharde tanden	Ja
Gewicht (kg)	0.4
weldedHub	Nee
execution	*
taperBushSize	
hubDiamDnMM	57
lengthInclHubLnMM	30

keywayAccToDIN6885/1	Ja
boreDiameterTol	H7
keywayTol	H9
setscrewSize	M8
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101350013032
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	32
Geharde tanden	Ja
Gewicht (kg)	0.4

Beschrijving

10B Simplex Z 13, Standard Finished Bore 32 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b113-32-neutral/>