

10B114 22 Neutral

SKU: 24110Z14B22H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	10B
designation	10B114 22
Boring diameter (mm)	22
Eenheden	pc
numberOfTeethZ	14
toothWidthMM	9.1
pitchCircleDiameterMM	71.34
tipCircleDiameterMM	78.2
Geharde tanden	Ja
Gewicht (kg)	0.51
weldedHub	Nee
taperBushSize	
hubDiamDnMM	52
lengthInclHubLnMM	30
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M5
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101350014022
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	22
Geharde tanden	Ja
Gewicht (kg)	0.51

Beschrijving

10B Simplex Z 14, Standard Finished Bore 22 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b114-22-neutral/>