

10B114 Neutral

SKU: 200KHM106Z14



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	ISO 606
designation	10B114
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	14
toothWidthMM	9.1
pilotBoreDiameterMM	12
pitchCircleDiameterMM	71.34
tipCircleDiameterMM	78.2
Geharde tanden	Ja
Gewicht (kg)	0.56
weldedHub	Nee
taperBushSize	
hubDiamDnMM	52
lengthInclHubLnMM	30

SprocketType	Standard Induction hardened teeth
BEAArticleNumber	191350014
ISOstandardSize2	10B
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	
Geharde tanden	Ja
Gewicht (kg)	0.56

Beschrijving

ISO 606 Simplex Z 14, Standard Induction hardened teeth Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b114-neutral-2/>