

10B115 28 Neutral

SKU: 24110Z15B28H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	10B
designation	10B115 28
Boring diameter (mm)	28
Eenheden	pc
numberOfTeethZ	15
toothWidthMM	9.1
pitchCircleDiameterMM	76.36
tipCircleDiameterMM	83.2
Geharde tanden	Ja
Gewicht (kg)	0.57
weldedHub	Nee
taperBushSize	
hubDiamDnMM	57
lengthInclHubLnMM	30
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M6
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101350015028
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	28
Geharde tanden	Ja
Gewicht (kg)	0.57

Beschrijving

10B Simplex Z 15, Standard Finished Bore 28 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b115-28-neutral/>