

10B117 20 Neutral

SKU: 24110Z17B20H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	10B
designation	10B117 20
Boring diameter (mm)	20
Eenheden	pc
numberOfTeethZ	17
toothWidthMM	9.1
pitchCircleDiameterMM	86.39
tipCircleDiameterMM	93.3
Geharde tanden	Ja
Gewicht (kg)	0.78
weldedHub	Nee
taperBushSize	
hubDiamDnMM	60
lengthInclHubLnMM	30
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M5
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101350017020
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	20
Geharde tanden	Ja
Gewicht (kg)	0.78

Beschrijving

10B Simplex Z 17, Standard Finished Bore 20 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b117-20-neutral/>