

10B117 Neutral

SKU: 200KHM106Z17



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	ISO 606
designation	10B117
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	17
toothWidthMM	9.1
pilotBoreDiameterMM	12
pitchCircleDiameterMM	86.39
tipCircleDiameterMM	93.3
Geharde tanden	Ja
Gewicht (kg)	0.88
weldedHub	Nee
taperBushSize	
hubDiamDnMM	60
lengthInclHubLnMM	30

SprocketType	Standard Induction hardened teeth
BEAArticleNumber	191350017
ISOstandardSize2	10B
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	
Geharde tanden	Ja
Gewicht (kg)	0.88

Beschrijving

ISO 606 Simplex Z 17, Standard Induction hardened teeth Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b117-neutral-2/>