

10B119 Neutral

SKU: 200KHM106Z19



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	ISO 606
designation	10B119
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	19
toothWidthMM	9.1
pilotBoreDiameterMM	14
pitchCircleDiameterMM	96.45
tipCircleDiameterMM	103.3
Geharde tanden	Ja
Gewicht (kg)	1.15
weldedHub	Nee
taperBushSize	
hubDiamDnMM	70
lengthInclHubLnMM	30

SprocketType	Standard Induction hardened teeth
BEAArticleNumber	191350019
ISOstandardSize2	10B
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	
Geharde tanden	Ja
Gewicht (kg)	1.15

Beschrijving

ISO 606 Simplex Z 19, Standard Induction hardened teeth Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b119-neutral-2/>