

10B120 32 Neutral

SKU: 24110Z20B32H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	10B
designation	10B120 32
Boring diameter (mm)	32
Eenheden	pc
numberOfTeethZ	20
toothWidthMM	9.1
pitchCircleDiameterMM	101.49
tipCircleDiameterMM	108.4
Geharde tanden	Ja
Gewicht (kg)	1.08
weldedHub	Nee
taperBushSize	
hubDiamDnMM	75
lengthInclHubLnMM	30
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M8
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101350020032
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	32
Geharde tanden	Ja
Gewicht (kg)	1.08

Beschrijving

10B Simplex Z 20, Standard Finished Bore 32 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b120-32-neutral/>