

10B122 35 Neutral

SKU: 24110Z22B35H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	10B
designation	10B122 35
Boring diameter (mm)	35
Eenheden	pc
numberOfTeethZ	22
toothWidthMM	9.1
pitchCircleDiameterMM	111.55
tipCircleDiameterMM	118.4
Geharde tanden	Ja
Gewicht (kg)	1.26
weldedHub	Nee
taperBushSize	
hubDiamDnMM	80
lengthInclHubLnMM	30
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M8
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101350022035
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	35
Geharde tanden	Ja
Gewicht (kg)	1.26

Beschrijving

10B Simplex Z 22, Standard Finished Bore 35 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b122-35-neutral/>