

10B125 19 Neutral

SKU: 24110Z25B19H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	10B
designation	10B125 19
Boring diameter (mm)	19
Eenheden	pc
numberOfTeethZ	25
toothWidthMM	9.1
pitchCircleDiameterMM	126.66
tipCircleDiameterMM	133.6
Geharde tanden	Ja
Gewicht (kg)	1.37
weldedHub	Nee
taperBushSize	
hubDiamDnMM	65
lengthInclHubLnMM	30
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M5
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101350025019
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	19
Geharde tanden	Ja
Gewicht (kg)	1.37

Beschrijving

10B Simplex Z 25, Standard Finished Bore 19 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b125-19-neutral/>