

10B130 Neutral

SKU: 200KHM106Z30



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	ISO 606
designation	10B130
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	30
toothWidthMM	9.1
pilotBoreDiameterMM	20
pitchCircleDiameterMM	151.87
tipCircleDiameterMM	158.8
Geharde tanden	Ja
Gewicht (kg)	2.41
weldedHub	Nee
taperBushSize	
hubDiamDnMM	90
lengthInclHubLnMM	35

SprocketType	Standard Induction hardened teeth
BEAArticleNumber	191350030
ISOstandardSize2	10B
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	
Geharde tanden	Ja
Gewicht (kg)	2.41

Beschrijving

ISO 606 Simplex Z 30, Standard Induction hardened teeth Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b130-neutral-2/>