


10B312 Neutral

SKU: 200KWTR106Z12



Specificaties

Kettingsontwerp	Triplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	10B
designation	10B312
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	12
toothWidthMM	42.1
pilotBoreDiameterMM	16
pitchCircleDiameterMM	61.34
tipCircleDiameterMM	68.2
Geharde tanden	Nee
Gewicht (kg)	0.78
weldedHub	Nee
taperBushSize	
hubDiamDnMM	44
lengthInclHubLnMM	55

toothWidthb1MM	9
SprocketType	Standard
BEAArticleNumber	103350012
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	
Geharde tanden	Nee
Gewicht (kg)	0.78

Beschrijving

10B Triplex Z 12, Standard Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b312-neutral/>