

10B315 Neutral

SKU: 200KWTR106Z15



Specificaties

Kettingsontwerp	Triplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	10B
designation	10B315
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	15
toothWidthMM	42.1
pilotBoreDiameterMM	16
pitchCircleDiameterMM	76.36
tipCircleDiameterMM	83.2
Geharde tanden	Nee
Gewicht (kg)	1.37
weldedHub	Nee
taperBushSize	
hubDiamDnMM	59
lengthInclHubLnMM	55

toothWidthb1MM	9
SprocketType	Standard
BEAArticleNumber	103350015
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	
Geharde tanden	Nee
Gewicht (kg)	1.37

Beschrijving

10B Triplex Z 15, Standard Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b315-neutral/>