

10B324 Neutral

SKU: 200KWTR106Z24



Specificaties

Kettingsontwerp	Triplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
ISO-standaardmaat	10B
designation	10B324
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	24
toothWidthMM	42.1
pilotBoreDiameterMM	20
pitchCircleDiameterMM	121.62
tipCircleDiameterMM	128.5
Geharde tanden	Nee
Gewicht (kg)	4.25
weldedHub	Nee
taperBushSize	
hubDiamDnMM	100
lengthInclHubLnMM	60

toothWidthb1MM	9
SprocketType	Standard
BEAArticleNumber	103350024
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	5/8"
Spoed (mm)	15.875
Boring diameter (mm)	
Geharde tanden	Nee
Gewicht (kg)	4.25

Beschrijving

10B Triplex Z 24, Standard Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/10b324-neutral/>