

## 10B327 Neutral

SKU: 200KWTR106Z27



## Specificaties

|                        |         |
|------------------------|---------|
| Kettingsontwerp        | Triplex |
| Oppervlaktebehandeling | No      |
| Materiaal              | C45     |
| Spoed (inch)           | 5/8"    |
| Spoed (mm)             | 15.875  |
| ISO-standaardmaat      | 10B     |
| designation            | 10B327  |
| Boring diameter (mm)   |         |
| Eenheden               | pc      |
| numberOfTeethZ         | 27      |
| toothWidthMM           | 42.1    |
| pilotBoreDiameterMM    | 20      |
| pitchCircleDiameterMM  | 136.75  |
| tipCircleDiameterMM    | 143.6   |
| Geharde tanden         | Nee     |
| Gewicht (kg)           | 5.43    |
| weldedHub              | Nee     |
| taperBushSize          |         |
| hubDiamDnMM            | 110     |
| lengthInclHubLnMM      | 60      |

|                                               |           |
|-----------------------------------------------|-----------|
| toothWidthb1MM                                | 9         |
| SprocketType                                  | Standard  |
| BEAArticleNumber                              | 103350027 |
| ISOstandardSize2                              | ISO 606   |
| brandType(extraAttributeForNeutralIdentifier) | Extended  |
| Merk                                          | Neutral   |
| Materiaal                                     | C45       |
| Spoed (inch)                                  | 5/8"      |
| Spoed (mm)                                    | 15.875    |
| Boring diameter (mm)                          |           |
| Geharde tanden                                | Nee       |
| Gewicht (kg)                                  | 5.43      |

# Beschrijving

10B Triplex Z 27, Standard Neutral Sprockets

# Product URL

<https://aandrijftechniek.nl/product/10b327-neutral/>