

11M1600JB/3 GATES Polyflex??? JB??? Banded V-belts GATES

SKU: 4G00011M1600/3



Specificaties

Type riem	Wide angle V-belts PU
Hoogte riem (mm)	7.1
Breedte riem (mm)	11
Antistatisch	Ja
Spoorlengte (mm)	1582
Materiaal riem	PU
Koordmateriaal	Polyester
Eenheden	pc
Riemprofiel	11M/JB
Gewicht (kg)	0.272
Omschrijving (EN)	<p>Polyflex??? JB??? is synonymous with high power density in small spaces. Developed by Gates and produced to patented manufacturing processes, these belts provide more load-carrying capacity at higher speeds to small multiple V-belt precision drives. This results in significant cost savings and improved design freedom. Polyflex??? JB??? belts are recommended for use on bench type milling machines, lathe drives, woodworking and metalworking machine spindle drives, computer peripheral equipment, small blowers, etc. They are available in 3M-JB, 5M-JB, 7M-JB and 11M-JB sections. High modulus polyurethane compound with a high friction coefficient. The polyurethane compound resists fatigue, wear and ozone. Temperature Range: -54??C to +85??C (-65??F to +185??F).</p>

Minimale temperatuur (??C)	-54
Maximale temperatuur (??C)	+85
EAN-code	5412571042825
Aangepaste code	3926.9097.90
numberOfRibs	3
Status	Normal
oringColour	BLACK
Land van herkomst	US
Constructie	Banded
beltInside	Smooth
beltBackSide	Notched
Hoek	60
Merk	GATES

Beschrijving

11M1600JB/3 GATES Polyflex??? JB??? Banded V-belts

Product URL

<https://aandrijftechniek.nl/product/11m1600jb-3-gates-polyflex-jb-banded-v-belts-gates/>