

## 12B112 28 Neutral

SKU: 24112Z12B28H



### Specificaties

<b>Kettingsontwerp</b>	Simplex
<b>Oppervlaktebehandeling</b>	NO
<b>Materiaal</b>	C45
<b>Spoed (inch)</b>	3/4"
<b>Spoed (mm)</b>	19.05
<b>ISO-standaardmaat</b>	12B
<b>designation</b>	12B112 28
<b>Boring diameter (mm)</b>	28
<b>Eenheden</b>	pc
<b>numberOfTeethZ</b>	12
<b>toothWidthMM</b>	11.1
<b>pitchCircleDiameterMM</b>	73.6
<b>tipCircleDiameterMM</b>	81.8
<b>Geharde tanden</b>	Ja
<b>Gewicht (kg)</b>	0.57
<b>weldedHub</b>	Nee
<b>taperBushSize</b>	
<b>hubDiamDnMM</b>	52
<b>lengthInclHubLnMM</b>	35
<b>keywayAccToDIN6885/1</b>	Ja

<b>boreDiameterTol</b>	H7
<b>keywayTol</b>	H9
<b>setscrewSize</b>	M6
<b>SprocketType</b>	Standard Finished Bore
<b>BEAArticleNumber</b>	SB101360012028
<b>ISOstandardSize2</b>	ISO 606
<b>brandType(extraAttributeForNeutralIdentifier)</b>	Extended
<b>Merk</b>	Neutral
<b>Materiaal</b>	C45
<b>Spoed (inch)</b>	3/4"
<b>Spoed (mm)</b>	19.05
<b>Boring diameter (mm)</b>	28
<b>Geharde tanden</b>	Ja
<b>Gewicht (kg)</b>	0.57

## Beschrijving

12B Simplex Z 12, Standard Finished Bore 28 Neutral Sprockets

## Product URL

<https://aandrijftechniek.nl/product/12b112-28-neutral/>