

12B113 32 Neutral

SKU: 24112Z13B32H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.05
ISO-standaardmaat	12B
designation	12B113 32
Boring diameter (mm)	32
Eenheden	pc
numberOfTeethZ	13
toothWidthMM	11.1
pitchCircleDiameterMM	79.59
tipCircleDiameterMM	87.8
Geharde tanden	Ja
Gewicht (kg)	0.66
weldedHub	Nee
taperBushSize	
hubDiamDnMM	58
lengthInclHubLnMM	35
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M8
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101360013032
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.05
Boring diameter (mm)	32
Geharde tanden	Ja
Gewicht (kg)	0.66

Beschrijving

12B Simplex Z 13, Standard Finished Bore 32 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/12b113-32-neutral/>