

12B114 Neutral

SKU: 200KHM127Z14



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.5
ISO-standaardmaat	ISO 606
designation	12B114
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	14
toothWidthMM	11.1
pilotBoreDiameterMM	16
pitchCircleDiameterMM	85.61
tipCircleDiameterMM	93.8
Geharde tanden	Ja
Gewicht (kg)	0.97
weldedHub	Nee
taperBushSize	
hubDiamDnMM	64
lengthInclHubLnMM	35

SprocketType	Standard Induction hardened teeth
BEAArticleNumber	191360014
ISOstandardSize2	12B
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.5
Boring diameter (mm)	
Geharde tanden	Ja
Gewicht (kg)	0.97

Beschrijving

ISO 606 Simplex Z 14, Standard Induction hardened teeth Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/12b114-neutral-2/>