

12B115 30 Neutral

SKU: 24112Z15B30H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.05
ISO-standaardmaat	12B
designation	12B115 30
Boring diameter (mm)	30
Eenheden	pc
numberOfTeethZ	15
toothWidthMM	11.1
pitchCircleDiameterMM	91.63
tipCircleDiameterMM	99.8
Geharde tanden	Ja
Gewicht (kg)	1.06
weldedHub	Nee
taperBushSize	
hubDiamDnMM	70
lengthInclHubLnMM	35
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M6
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101360015030
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.05
Boring diameter (mm)	30
Geharde tanden	Ja
Gewicht (kg)	1.06

Beschrijving

12B Simplex Z 15, Standard Finished Bore 30 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/12b115-30-neutral/>