

12B115 Neutral

SKU: 200KHM127Z15



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.5
ISO-standaardmaat	ISO 606
designation	12B115
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	15
toothWidthMM	11.1
pilotBoreDiameterMM	16
pitchCircleDiameterMM	91.63
tipCircleDiameterMM	99.8
Geharde tanden	Ja
Gewicht (kg)	1.16
weldedHub	Nee
taperBushSize	
hubDiamDnMM	70
lengthInclHubLnMM	35

SprocketType	Standard Induction hardened teeth
BEAArticleNumber	191360015
ISOstandardSize2	12B
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.5
Boring diameter (mm)	
Geharde tanden	Ja
Gewicht (kg)	1.16

Beschrijving

ISO 606 Simplex Z 15, Standard Induction hardened teeth Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/12b115-neutral-2/>