

12B116 20 Neutral

SKU: 24112Z16B20H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.05
ISO-standaardmaat	12B
designation	12B116 20
Boring diameter (mm)	20
Eenheden	pc
numberOfTeethZ	16
toothWidthMM	11.1
pitchCircleDiameterMM	97.65
tipCircleDiameterMM	105.8
Geharde tanden	Ja
Gewicht (kg)	1.15
weldedHub	Nee
taperBushSize	
hubDiamDnMM	65
lengthInclHubLnMM	35
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M5
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101360016020
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.05
Boring diameter (mm)	20
Geharde tanden	Ja
Gewicht (kg)	1.15

Beschrijving

12B Simplex Z 16, Standard Finished Bore 20 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/12b116-20-neutral/>