

12B118 Neutral

SKU: 200KHM127Z18



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.5
ISO-standaardmaat	ISO 606
designation	12B118
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	18
toothWidthMM	11.1
pilotBoreDiameterMM	16
pitchCircleDiameterMM	109.71
tipCircleDiameterMM	117.9
Geharde tanden	Ja
Gewicht (kg)	1.62
weldedHub	Nee
taperBushSize	
hubDiamDnMM	80
lengthInclHubLnMM	35

SprocketType	Standard Induction hardened teeth
BEAArticleNumber	191360018
ISOstandardSize2	12B
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.5
Boring diameter (mm)	
Geharde tanden	Ja
Gewicht (kg)	1.62

Beschrijving

ISO 606 Simplex Z 18, Standard Induction hardened teeth Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/12b118-neutral-2/>