

12B119 50 Neutral

SKU: 24112Z19B50H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.05
ISO-standaardmaat	12B
designation	12B119 50
Boring diameter (mm)	50
Eenheden	pc
numberOfTeethZ	19
toothWidthMM	11.1
pitchCircleDiameterMM	115.75
tipCircleDiameterMM	123.9
Geharde tanden	Ja
Gewicht (kg)	1.25
weldedHub	Nee
taperBushSize	
hubDiamDnMM	80
lengthInclHubLnMM	35
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M12
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101360019050
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.05
Boring diameter (mm)	50
Geharde tanden	Ja
Gewicht (kg)	1.25

Beschrijving

12B Simplex Z 19, Standard Finished Bore 50 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/12b119-50-neutral/>