

12B121 30 Neutral

SKU: 24112Z21B30H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.05
ISO-standaardmaat	12B
designation	12B121 30
Boring diameter (mm)	30
Eenheden	pc
numberOfTeethZ	21
toothWidthMM	11.1
pitchCircleDiameterMM	127.82
tipCircleDiameterMM	136
Geharde tanden	Ja
Gewicht (kg)	1.97
weldedHub	Nee
taperBushSize	
hubDiamDnMM	80
lengthInclHubLnMM	40
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M6
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101360021030
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.05
Boring diameter (mm)	30
Geharde tanden	Ja
Gewicht (kg)	1.97

Beschrijving

12B Simplex Z 21, Standard Finished Bore 30 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/12b121-30-neutral/>