

12B122 35 Neutral

SKU: 24112Z22B35H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.05
ISO-standaardmaat	12B
designation	12B122 35
Boring diameter (mm)	35
Eenheden	pc
numberOfTeethZ	22
toothWidthMM	11.1
pitchCircleDiameterMM	133.86
tipCircleDiameterMM	142
Geharde tanden	Ja
Gewicht (kg)	2.31
weldedHub	Nee
taperBushSize	
hubDiamDnMM	90
lengthInclHubLnMM	40
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M8
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101360022035
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.05
Boring diameter (mm)	35
Geharde tanden	Ja
Gewicht (kg)	2.31

Beschrijving

12B Simplex Z 22, Standard Finished Bore 35 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/12b122-35-neutral/>