

## 12B122 38 Neutral

SKU: 24112Z22B38H



### Specificaties

|                               |           |
|-------------------------------|-----------|
| <b>Kettingsontwerp</b>        | Simplex   |
| <b>Oppervlaktebehandeling</b> | NO        |
| <b>Materiaal</b>              | C45       |
| <b>Spoed (inch)</b>           | 3/4"      |
| <b>Spoed (mm)</b>             | 19.05     |
| <b>ISO-standaardmaat</b>      | 12B       |
| <b>designation</b>            | 12B122 38 |
| <b>Boring diameter (mm)</b>   | 38        |
| <b>Eenheden</b>               | pc        |
| <b>numberOfTeethZ</b>         | 22        |
| <b>toothWidthMM</b>           | 11.1      |
| <b>pitchCircleDiameterMM</b>  | 133.86    |
| <b>tipCircleDiameterMM</b>    | 142       |
| <b>Geharde tanden</b>         | Ja        |
| <b>Gewicht (kg)</b>           | 2.26      |
| <b>weldedHub</b>              | Nee       |
| <b>taperBushSize</b>          |           |
| <b>hubDiamDnMM</b>            | 90        |
| <b>lengthInclHubLnMM</b>      | 40        |
| <b>keywayAccToDIN6885/1</b>   | Ja        |

|  |                        |
|--|------------------------|
| <b>boreDiameterTol</b>                               | H7                     |
| <b>keywayTol</b>                                     | H9                     |
| <b>setscrewSize</b>                                  | M8                     |
| <b>SprocketType</b>                                  | Standard Finished Bore |
| <b>BEAArticleNumber</b>                              | SB101360022038         |
| <b>ISOstandardSize2</b>                              | ISO 606                |
| <b>brandType(extraAttributeForNeutralIdentifier)</b> | Extended               |
| <b>Merk</b>  | Neutral                |
| <b>Materiaal</b>                                     | C45                    |
| <b>Spoed (inch)</b>                                  | 3/4"                   |
| <b>Spoed (mm)</b>                                    | 19.05                  |
| <b>Boring diameter (mm)</b>                          | 38                     |
| <b>Geharde tanden</b>                                | Ja                     |
| <b>Gewicht (kg)</b>                                  | 2.26                   |

## Beschrijving

12B Simplex Z 22, Standard Finished Bore 38 Neutral Sprockets

## Product URL

<https://aandrijftechniek.nl/product/12b122-38-neutral/>