

12B122 Neutral

SKU: 200KHM127Z22



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.5
ISO-standaardmaat	ISO 606
designation	12B122
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	22
toothWidthMM	11.1
pilotBoreDiameterMM	20
pitchCircleDiameterMM	133.86
tipCircleDiameterMM	142
Geharde tanden	Ja
Gewicht (kg)	2.46
weldedHub	Nee
taperBushSize	
hubDiamDnMM	90
lengthInclHubLnMM	40

SprocketType	Standard Induction hardened teeth
BEAArticleNumber	191360022
ISOstandardSize2	12B
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.5
Boring diameter (mm)	
Geharde tanden	Ja
Gewicht (kg)	2.46

Beschrijving

ISO 606 Simplex Z 22, Standard Induction hardened teeth Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/12b122-neutral-2/>