

12B124 25 Neutral

SKU: 24112Z24B25



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.05
ISO-standaardmaat	12B
designation	12B124 25
Boring diameter (mm)	25
Eenheden	pc
numberOfTeethZ	24
toothWidthMM	11.1
pitchCircleDiameterMM	145.94
tipCircleDiameterMM	154.1
Geharde tanden	Ja
Gewicht (kg)	2.14
weldedHub	Nee
taperBushSize	
hubDiamDnMM	70
lengthInclHubLnMM	40
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M6
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101360024025
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	3/4"
Spoed (mm)	19.05
Boring diameter (mm)	25
Geharde tanden	Ja
Gewicht (kg)	2.14

Beschrijving

12B Simplex Z 24, Standard Finished Bore 25 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/12b124-25-neutral/>