

12B124 40 Neutral

SKU: 24112Z24B40



Specificaties

| | |
|-------------------------------|-----------|
| Kettingsontwerp | Simplex |
| Oppervlaktebehandeling | NO |
| Materiaal | C45 |
| Spoed (inch) | 3/4" |
| Spoed (mm) | 19.05 |
| ISO-standaardmaat | 12B |
| designation | 12B124 40 |
| Boring diameter (mm) | 40 |
| Eenheden | pc |
| numberOfTeethZ | 24 |
| toothWidthMM | 11.1 |
| pitchCircleDiameterMM | 145.94 |
| tipCircleDiameterMM | 154.1 |
| Geharde tanden | Ja |
| Gewicht (kg) | 2.44 |
| weldedHub | Nee |
| taperBushSize | |
| hubDiamDnMM | 90 |
| lengthInclHubLnMM | 40 |
| keywayAccToDIN6885/1 | Ja |

| | |
|--|------------------------|
| boreDiameterTol | H7 |
| keywayTol | H9 |
| setscrewSize | M10 |
| SprocketType | Standard Finished Bore |
| BEAArticleNumber | SB101360024040 |
| ISOstandardSize2 | ISO 606 |
| brandType(extraAttributeForNeutralIdentifier) | Extended |
| Merk | Neutral |
| Materiaal | C45 |
| Spoed (inch) | 3/4" |
| Spoed (mm) | 19.05 |
| Boring diameter (mm) | 40 |
| Geharde tanden | Ja |
| Gewicht (kg) | 2.44 |

Beschrijving

12B Simplex Z 24, Standard Finished Bore 40 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/12b124-40-neutral/>