

## 12B127 Neutral

SKU: 200KWM127Z27



## Specificaties

|                        |         |
|------------------------|---------|
| Kettingsontwerp        | Simplex |
| Oppervlaktebehandeling | No      |
| Materiaal              | C45     |
| Spoed (inch)           | 3/4"    |
| Spoed (mm)             | 19.05   |
| ISO-standaardmaat      | 12B     |
| designation            | 12B127  |
| Boring diameter (mm)   |         |
| Eenheden               | pc      |
| numberOfTeethZ         | 27      |
| toothWidthMM           | 11.1    |
| pilotBoreDiameterMM    | 20      |
| pitchCircleDiameterMM  | 164.09  |
| tipCircleDiameterMM    | 172.3   |
| Geharde tanden         | Nee     |
| Gewicht (kg)           | 3.21    |
| weldedHub              | Nee     |
| taperBushSize          |         |
| hubDiamDnMM            | 95      |
| lengthInclHubLnMM      | 40      |

|                                                      |           |
|------------------------------------------------------|-----------|
| <b>SprocketType</b>                                  | Standard  |
| <b>BEAArticleNumber</b>                              | 101360027 |
| <b>ISOstandardSize2</b>                              | ISO 606   |
| <b>brandType(extraAttributeForNeutralIdentifier)</b> | Extended  |
| <b>Merk</b>                                          | Neutral   |
| <b>Materiaal</b>                                     | C45       |
| <b>Spoed (inch)</b>                                  | 3/4"      |
| <b>Spoed (mm)</b>                                    | 19.05     |
| <b>Boring diameter (mm)</b>                          |           |
| <b>Geharde tanden</b>                                | Nee       |
| <b>Gewicht (kg)</b>                                  | 3.21      |

## Beschrijving

12B Simplex Z 27, Standard Neutral Sprockets

## Product URL

<https://aandrijftechniek.nl/product/12b127-neutral/>